

FAG 32922参数

尺寸	d	110	mm	-	
	D	150	mm	-	
	T	25	mm	-	
	a	26	mm	-	
	B	25	mm	-	
	C	20	mm	-	
	$C_{a \min}$	5	mm	-	
	$C_{b \min}$	5	mm	-	
	$D_{a \max}$	141	mm	-	
	$D_{a \min}$	140	mm	-	
	$D_{b \min}$	145	mm	-	
	d_1	130.9	mm	-	
	$d_{a \max}$	118	mm	-	
	$d_{b \min}$	117	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1260	g	质量
	基本额定载荷	C_r	133000	N	基本额定动载荷，径向
C_{0r}		231000	N	基本额定静载荷，径向	
计算系数	e	0.36		-	
	Y	1.69		-	
	Y_0	0.93		-	
疲劳极限载荷	C_{ur}	27000	N	疲劳极限载荷，径向	
极限转速	n_G	4550	r/min	极限转速	
参考转速	n_B	2500	r/min	参考速度	

FAG 32922图片

