

FAG NU256-E-TB-M1参数

| | | | | |
|--------|---------------------|---------|-------|-------------|
| 尺寸 | d | 280 | mm | - |
| | D | 500 | mm | - |
| | B | 80 | mm | - |
| | D ₁ | 426.6 | mm | - |
| | D _{a max} | 480 | mm | - |
| | d _{a max} | 334 | mm | - |
| | d _{a min} | 300 | mm | - |
| | d _{b min} | 340 | mm | - |
| | E | 449 | mm | - |
| | F | 337 | mm | - |
| | r _{1 min} | 5 | mm | - |
| | r _{a max} | 4 | mm | - |
| | r _{al max} | 4 | mm | - |
| | r _{min} | 5 | mm | - |
| | s | 6.3 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 72100 | g | 质量 |
| 基本额定载荷 | C _r | 1400000 | N | 基本额定动载荷，径向 |
| | C _{0r} | 2020000 | N | 基本额定静载荷，径向 |
| 极限转速 | n _G | 2020 | r/min | 极限转速 |
| 参考转速 | n _B | 1040 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 139000 | N | 疲劳极限载荷，径向 |

FAG NU256-E-TB-M1图片



参考资料:<http://www.sozhou.com/p/1561699d.html>

