



SKF S71915 CB/P4A参数

主要尺寸	d	75	mm	-
	D	105	mm	-
	B	16	mm	-
基本额定载荷	C	14000	N	动载荷
	C_0	13200	N	静载荷
疲劳载荷极限	P_u	560	N	-
可达转速	Grease	17000	r/min	-
	Oil-air	-	r/min	-
重量	重量	380	g	-
型号	型号	S71915 CB/P4A	-	-

SKF S71915 CB/P4A图片



Ball diameter 6,35

Number of balls 34

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
46	92	275	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
46	60	96	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 9,9

for preload in mounted bearing sets

f 1,11

f_1 1

f_{2A} 1




f_{2B} 1,02

f_{2C} 1,07

f_{2D} -

f_{HC} 1

参考资料:<http://www.sozhou.com/p/1d654763.html>



Ball diameter 6,35

Number of balls 34

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
46	92	275	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
46	60	96	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f₀ 9,9

for preload in mounted bearing sets

f 1,11

f₁ 1

f_{2A} 1

f_{2B} 1,02

f_{2C} 1,07

f_{2D} -

f_{HC} 1