

FAG 32028-X参数

尺寸	d	140	mm	-	
	D	210	mm	-	
	T	45	mm	-	
	a	46	mm	-	
	B	45	mm	-	
	C	34	mm	-	
	$C_{a \text{ min}}$	8	mm	-	
	$C_{b \text{ min}}$	11	mm	-	
	$D_{a \text{ max}}$	200	mm	-	
	$D_{a \text{ min}}$	187	mm	-	
	$D_{b \text{ min}}$	202	mm	-	
	d_1	175.8	mm	-	
	$d_{a \text{ max}}$	153	mm	-	
	$d_{b \text{ min}}$	150	mm	-	
	$r_{1, 2 \text{ min}}$	2.5	mm	-	
	$r_{3, 4 \text{ min}}$	2	mm	-	
	$r_{a \text{ max}}$	2.5	mm	-	
	$r_{b \text{ max}}$	2	mm	-	
	重量	m	5340	g	质量
	基本额定载荷	C_r	340000	N	基本额定动载荷，径向
C_{0r}		590000	N	基本额定静载荷，径向	
计算系数	e	0.46		-	
	Y	1.31		-	
	Y_0	0.72		-	
疲劳极限载荷	C_{ur}	65000	N	疲劳极限载荷，径向	
极限转速	n_G	3150	r/min	极限转速	
参考转速	n_B	2170	r/min	参考速度	

FAG 32028-X图片

