

## NACHI 29317EX参数

|        |           |         |       |      |
|--------|-----------|---------|-------|------|
| 外形尺寸   | d         | 85      | mm    | 内径   |
|        | D         | 150     | mm    | 外径   |
|        | T         | 39      | mm    | 宽度   |
|        | r         | 1.5~3.5 | mm    | 倒角   |
| 参考尺寸   | d1        | 134     | mm    | -    |
|        | D1        | 110.5   | mm    | -    |
|        | B         | 25      | mm    | -    |
|        | B1        | 35      | mm    | -    |
|        | C         | 19      | mm    | -    |
|        | A         | 50      | mm    | -    |
| 安装尺寸   | da (min)  | 115     | mm    | (最小) |
|        | Da (max)  | 135     | mm    | (最大) |
|        | ra (max)  | 1.5     | mm    | (最大) |
|        | db1 (max) | 90      | mm    | (最大) |
|        | db2 (max) | 90      | mm    | (最大) |
| 重量     | Mass      | 2670    | g     | 重量   |
| 基本额定载荷 | Ca        | 365000  | N     | 动载荷  |
|        | Coa       | 1060000 | N     | 静载荷  |
| 极限速度   | Grease    | 1600    | r/min | 脂润滑  |
|        | Oil       | 2700    | r/min | 油润滑  |

## NACHI 29317EX图片

参考资料:<http://www.sozhou.com/p/2f7068d9.html>

