

FAG 32015-X-XL 参数

尺寸	d	75	mm	-	
	D	115	mm	-	
	T	25	mm	-	
	a	25.5	mm	-	
	B	25	mm	-	
	C	19	mm	-	
	$C_{a \text{ min}}$	5	mm	-	
	$C_{b \text{ min}}$	6	mm	-	
	$D_{a \text{ max}}$	108	mm	-	
	$D_{a \text{ min}}$	103	mm	-	
	d_1	97	mm	-	
	$d_{a \text{ max}}$	83	mm	-	
	$d_{b \text{ min}}$	82	mm	-	
	$r_{1, 2 \text{ min}}$	1.5	mm	-	
	$r_{3, 4 \text{ min}}$	1.5	mm	-	
	$r_{a \text{ max}}$	1.5	mm	-	
	$r_{b \text{ max}}$	1.5	mm	-	
	重量	m	920	g	质量
	基本额定载荷	C_r	124000	N	基本额定动载荷, 径向
		C_{0r}	165000	N	基本额定静载荷, 径向
计算系数	e	0.46		-	
	Y	1.31		-	
	Y_0	0.72		-	
疲劳极限载荷	C_{ur}	25500	N	疲劳极限载荷, 径向	
极限转速	n_G	6000	r/min	极限转速	
参考转速	n_B	3600	r/min	参考速度	
说明		T4CC075		根据 DIN ISO 355 的 对应型号	

尺寸	D_b min	110	mm	-
----	-----------	-----	----	---

FAG 32015-X-XL图片

