

NSK NJ422参数

| | | | | |
|--------|------|-----------|-------|------|
| 安装尺寸 | DBB2 | 151 | mm | (最大) |
| | DC | 157 | mm | (最小) |
| | DD1 | 173 | mm | (最小) |
| | DA2 | 264.0 | mm | (最大) |
| | DB1 | 0.0 | mm | (最小) |
| | DB2 | 0.0 | mm | (最小) |
| | RA | 3.0 | mm | (最大) |
| | RB | 3.0 | mm | (最大) |
| | 重量 | MASS | 22100 | g |
| 型号 | 型号 | NJ422 | | - |
| 外形尺寸 | SD | 110 | mm | 内径 |
| | D | 280 | mm | 外径 |
| | B | 65 | mm | 宽度 |
| | R | 4.0 | mm | (最小) |
| | R1 | 4.0 | mm | (最小) |
| | FW | 155.0 | mm | - |
| | EW | 0.0 | mm | - |
| 基本额定载荷 | CR1 | 550000 | N | 动载荷 |
| | COR1 | 620000 | N | 静载荷 |
| | CR2 | 56000 | kgf | 动载荷 |
| | COR2 | 63500 | kgf | 静载荷 |
| 极限转速 | LG | 2200 | 1/min | 脂润滑 |
| | LO | 2800 | 1/min | 油润滑 |
| 安装尺寸 | DA1 | 126.0 | mm | (最小) |
| | DBB1 | 126.00000 | mm | (最小) |

NSK NJ422图片

参考资料:<http://www.sozhou.com/p/3da0c413.html>

