

FAG 23192-K-MB + AHX3192G参数

尺寸	$d_{1H}$	440	mm	-
	D	760	mm	-
	B	240	mm	-
	a	11	mm	-
	b	43	mm	-
	$D_1$	661.4	mm	-
	$D_{a\ max}$	728	mm	-
	d	460	mm	-
	$d_{2G}$	Tr480x5		-
	$d_{a\ min}$	492	mm	-
	$d_s$	12.5	mm	-
	l	285	mm	-
	$n_s$	23.5	mm	-
	$r_{a\ max}$	6	mm	-
	$r_{min}$	7.5	mm	-
说明		AHX3192G		型号, 退卸套
重量	m	420000	g	质量
	$m_1$	50300	g	质量, 退卸套
基本额定载荷	$C_r$	5850000	N	基本额定动载荷, 径向
计算系数	e	0.32		-
	$Y_1$	2.12		-
	$Y_2$	3.15		-
基本额定载荷	$C_{0r}$	11600000	N	基本额定静载荷, 径向
计算系数	$Y_0$	2.07		-
极限转速	$n_G$	770	r/min	极限转速
参考转速	$n_B$	400	r/min	参考速度
疲劳极限载荷	$C_{ur}$	530000	N	疲劳极限载荷, 径向

FAG 23192-K-MB + AHX3192G图片



参考资料:<http://www.sozhou.com/p/3fad6650.html>