

FAG 30315-A参数

尺寸	$C_{a \min}$	5	mm	-
	$C_{b \min}$	9	mm	-
	$D_{a \max}$	148	mm	-
	$D_{a \min}$	139	mm	-
	$D_{b \min}$	149	mm	-
	d_1	114	mm	-
	$d_{a \max}$	95	mm	-
	$d_{b \min}$	87	mm	-
	$r_{1, 2 \min}$	3	mm	-
	$r_{3, 4 \min}$	2.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	3640	g	质量
基本额定载荷	C_r	250000	N	基本额定动载荷，径向
	C_{0r}	295000	N	基本额定静载荷，径向
计算系数	e	0.35		-
	Y	1.74		-
	Y_0	0.96		-
疲劳极限载荷	C_{ur}	34500	N	疲劳极限载荷，径向
极限转速	n_G	4600	r/min	极限转速
参考转速	n_B	3500	r/min	参考速度
说明		T2GB075		根据 DIN ISO 355 的 对应型号
尺寸	d	75	mm	-
	D	160	mm	-
	T	40	mm	-
	a	32	mm	-
	B	37	mm	-

FAG 30315-A图片

