

NACHI 6303ZENR参数

| | | | | |
|--------|-----------|-------|-------|------|
| 外形尺寸 | d | 17 | mm | 内径 |
| | D | 47 | mm | 外径 |
| | B | 14 | mm | 宽度 |
| | r | 1~1.5 | mm | 轴向 |
| | r | 1~3 | mm | 轴向 |
| | r1 | 0.5~ | mm | 径向 |
| | r1 | 0.5~ | mm | 径向 |
| | 止动槽和止动环尺寸 | D1 | 44.6 | mm |
| a | | 2.46 | mm | (最大) |
| D2 | | 52.7 | mm | (最大) |
| f | | 1.12 | mm | (最大) |
| 安装尺寸 | da(min) | 23 | mm | (最小) |
| | Da(max) | 41 | mm | (最大) |
| | Dx(min) | 53.5 | mm | (最小) |
| | ra(max) | 1 | mm | (最大) |
| | Cy(max) | 3.3 | mm | (最大) |
| 基本额定载荷 | Cr | 13600 | N | 动载荷 |
| | Cor | 6550 | N | 静载荷 |
| 极限速度 | Grease | 15000 | r/min | 脂润滑 |
| | Oil | 18000 | r/min | 油润滑 |

NACHI 6303ZENR图片

参考资料:<http://www.sozhou.com/p/412dd9fe.html>

