

NSK NU407参数

| | | | | |
|--------|------|----------|-------|------|
| 型号 | 型号 | NU407 | | - |
| 外形尺寸 | SD | 35 | mm | 内径 |
| | D | 100 | mm | 外径 |
| | B | 25 | mm | 宽度 |
| | R | 1.5 | mm | (最小) |
| | R1 | 1.5 | mm | (最小) |
| | FW | 53.0 | mm | - |
| | EW | 83.0 | mm | - |
| 基本额定载荷 | CR1 | 75500 | N | 动载荷 |
| | COR1 | 69000 | N | 静载荷 |
| | CR2 | 7700 | kgf | 动载荷 |
| | COR2 | 7050 | kgf | 静载荷 |
| 极限转速 | LG | 6700 | 1/min | 脂润滑 |
| | LO | 8000 | 1/min | 油润滑 |
| 安装尺寸 | DA1 | 43.0 | mm | (最小) |
| | DBB1 | 43.00000 | mm | (最小) |
| | DBB2 | 51 | mm | (最大) |
| | DC | 55 | mm | (最小) |
| | DD1 | 61 | mm | (最小) |
| | DA2 | 92.0 | mm | (最大) |
| | DB1 | 92.0 | mm | (最小) |
| | DB2 | 85.0 | mm | (最小) |
| | RA | 1.5 | mm | (最大) |
| | RB | 1.5 | mm | (最大) |
| 重量 | MASS | 1010 | g | 重量 |

NSK NU407图片

参考资料:<http://www.sozhou.com/p/44d3a984.html>

