

FAG 33009参数

尺寸	B	24	mm	-	
	C	19	mm	-	
	$C_{a \min}$	4	mm	-	
	$C_{b \min}$	5	mm	-	
	$D_{a \max}$	69	mm	-	
	$D_{a \min}$	67	mm	-	
	$D_{b \min}$	71	mm	-	
	d_1	61.8	mm	-	
	$d_{a \max}$	51	mm	-	
	$d_{b \min}$	51	mm	-	
	$r_{1, 2 \min}$	1	mm	-	
	$r_{3, 4 \min}$	1	mm	-	
	$r_{a \max}$	1	mm	-	
	$r_{b \max}$	1	mm	-	
	重量	m	432	g	质量
	基本额定载荷	C_r	71000	N	基本额定动载荷，径向
C_{0r}		103000	N	基本额定静载荷，径向	
计算系数	e	0.29		-	
	Y	2.04		-	
	Y_0	1.12		-	
疲劳极限载荷	C_{ur}	12700	N	疲劳极限载荷，径向	
极限转速	n_G	9400	r/min	极限转速	
参考转速	n_B	5900	r/min	参考速度	
说明		T2CE045		根据 DIN ISO 355 的 对应型号	
尺寸	d	45	mm	-	
	D	75	mm	-	
	T	24	mm	-	

FAG 33009图片

