

FAG NJ2207-E-TVP2 + HJ2207-E参数

尺寸	d	35	mm	-
	D	72	mm	-
	B	23	mm	-
	B <sub>1</sub>	4	mm	-
	B <sub>2</sub>	8.5	mm	-
重量	m	416	g	质量
	m <sub>1</sub>	35	g	质量, L 型圈
基本额定载荷	C <sub>r</sub>	73000	N	基本额定动载荷, 径向
	C <sub>0r</sub>	65000	N	基本额定静载荷, 径向
极限转速	n <sub>G</sub>	12300	r/min	极限转速
参考转速	n <sub>B</sub>	7400	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	10500	N	疲劳极限载荷, 径向
尺寸	D <sub>1</sub>	61	mm	-
	D <sub>a max</sub>	65	mm	-
	d <sub>1</sub>	48	mm	-
	d <sub>a max</sub>	43	mm	-
	d <sub>a min</sub>	39	mm	-
	d <sub>c min</sub>	50	mm	-
	E	64	mm	-
	F	44	mm	-
	r <sub>1 min</sub>	0.6	mm	-
	r <sub>a max</sub>	1	mm	-
	r <sub>al max</sub>	0.6	mm	-
	r <sub>min</sub>	1.1	mm	-
	s	2.2	mm	距离中心位置的轴向偏移
	说明		HJ2207-E	



