

FAG 24080-B-K30-MB + AH24080参数

尺寸	d_{1H}	380	mm	-
	D	600	mm	-
	B	200	mm	-
	a	20	mm	-
	b	28	mm	-
	D_1	530.9	mm	-
	$D_{a \max}$	582	mm	-
	d	400	mm	-
	d_{2G}	Tr420x5		-
	$d_{a \min}$	418	mm	-
	d_s	12.5	mm	-
	l	228	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	4	mm	-
	r_{\min}	5	mm	-
说明		AH24080		型号, 退卸套
重量	m	196000	g	质量
	m_1	27800	g	质量, 退卸套
基本额定载荷	C_r	3900000	N	基本额定动载荷, 径向
计算系数	e	0.33		-
	Y_1	2.06		-
	Y_2	3.06		-
基本额定载荷	C_{0r}	8500000	N	基本额定静载荷, 径向
计算系数	Y_0	2.01		-
极限转速	n_G	910	r/min	极限转速
参考转速	n_B	490	r/min	参考速度
疲劳极限载荷	C_{ur}	670000	N	疲劳极限载荷, 径向

FAG 24080-B-K30-MB + AH24080图片



参考资料:<http://www.sozhou.com/p/4b47c360.html>