

NSK NJ2315参数

| | | | | | |
|--------|------|----------|--------|------|----|
| 极限转速 | L0 | 4300 | 1/min | 油润滑 | |
| 安装尺寸 | DA1 | 86.0 | mm | (最小) | |
| | DBB1 | 86.00000 | mm | (最小) | |
| | DBB2 | 93 | mm | (最大) | |
| | DC | 97 | mm | (最小) | |
| | DD1 | 106 | mm | (最小) | |
| | DA2 | 149.0 | mm | (最大) | |
| | DB1 | 0.0 | mm | (最小) | |
| | DB2 | 0.0 | mm | (最小) | |
| | RA | 2.0 | mm | (最大) | |
| | RB | 2.0 | mm | (最大) | |
| | 重量 | MASS | 4910 | g | 重量 |
| | 型号 | 型号 | NJ2315 | | - |
| 外形尺寸 | SD | 75 | mm | 内径 | |
| | D | 160 | mm | 外径 | |
| | B | 55 | mm | 宽度 | |
| | R | 2.1 | mm | (最小) | |
| | R1 | 2.1 | mm | (最小) | |
| | FW | 95.5 | mm | - | |
| | EW | 0.0 | mm | - | |
| 基本额定载荷 | CR1 | 258000 | N | 动载荷 | |
| | COR1 | 300000 | N | 静载荷 | |
| | CR2 | 26300 | kgf | 动载荷 | |
| | COR2 | 31000 | kgf | 静载荷 | |
| 极限转速 | LG | 3400 | 1/min | 脂润滑 | |

NSK NJ2315图片

参考资料:<http://www.sozhou.com/p/519ba374.html>

