

FAG 23940-S-K-MB + AH3940参数

尺寸	d_{1H}	190	mm	-
	D	280	mm	-
	B	60	mm	-
	a	6	mm	-
	b	16	mm	-
	D_1	256.9	mm	-
	$D_{a\ max}$	269.8	mm	-
	d	200	mm	-
	d_{2G}	Tr210x4		-
	$d_{a\ min}$	210.2	mm	-
	d_s	6.3	mm	-
	l	77	mm	-
	n_s	12.2	mm	-
	$r_{a\ max}$	2.1	mm	-
	r_{min}	2.1	mm	-
说明		AH3940		型号, 退卸套
重量	m	11500	g	质量
	m_1	2620	g	质量, 退卸套
基本额定载荷	C_r	550000	N	基本额定动载荷, 径向
计算系数	e	0.2		-
	Y_1	3.42		-
	Y_2	5.09		-
基本额定载荷	C_{0r}	1080000	N	基本额定静载荷, 径向
计算系数	Y_0	3.34		-
极限转速	n_G	2800	r/min	极限转速
参考转速	n_B	1670	r/min	参考速度
疲劳极限载荷	C_{ur}	71000	N	疲劳极限载荷, 径向

FAG 23940-S-K-MB + AH3940图片



参考资料:<http://www.sozhou.com/p/5864d7a2.html>