

## FAG 33011参数

尺寸	d	55	mm	-	
	D	90	mm	-	
	T	27	mm	-	
	a	19	mm	-	
	B	27	mm	-	
	C	21	mm	-	
	$C_{a \min}$	5	mm	-	
	$C_{b \min}$	6	mm	-	
	$D_{a \max}$	83	mm	-	
	$D_{a \min}$	81	mm	-	
	$D_{b \min}$	86	mm	-	
	$d_1$	74.2	mm	-	
	$d_{a \max}$	63	mm	-	
	$d_{b \min}$	62	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	673	g	质量
	基本额定载荷	$C_r$	94000	N	基本额定动载荷，径向
$C_{0r}$		142000	N	基本额定静载荷，径向	
计算系数	e	0.31		-	
	Y	1.92		-	
参考转速	$n_B$	4950	r/min	参考速度	
说明		T2CE055		根据 DIN ISO 355 的 对应型号	
计算系数	$Y_0$	1.06		-	
疲劳极限载荷	$C_{ur}$	18000	N	疲劳极限载荷，径向	

FAG 33011图片

