

## FAG 30234-A参数

尺寸	d	170	mm	-	
	D	310	mm	-	
	T	57	mm	-	
	a	60	mm	-	
	B	52	mm	-	
	C	43	mm	-	
	$C_a \text{ min}$	8	mm	-	
	$C_b \text{ min}$	14	mm	-	
	$D_a \text{ max}$	292	mm	-	
	$D_a \text{ min}$	269	mm	-	
	$D_b \text{ min}$	288	mm	-	
	$d_1$	233	mm	-	
	$d_a \text{ max}$	203	mm	-	
	$d_b \text{ min}$	188	mm	-	
	$r_{1, 2} \text{ min}$	5	mm	-	
	$r_{3, 4} \text{ min}$	4	mm	-	
	$r_a \text{ max}$	5	mm	-	
	$r_b \text{ max}$	4	mm	-	
	重量	m	16800	g	质量
	基本额定载荷	$C_r$	590000	N	基本额定动载荷, 径向
$C_{0r}$		810000	N	基本额定静载荷, 径向	
计算系数	e	0.44		-	
	Y	1.38		-	
	$Y_0$	0.76		-	
疲劳极限载荷	$C_{ur}$	90000	N	疲劳极限载荷, 径向	
极限转速	$n_G$	2280	r/min	极限转速	
参考转速	$n_B$	1590	r/min	参考速度	

FAG 30234-A图片

