

FAG 32060-X参数

尺寸	D	460	mm	-	
	T	100	mm	-	
	a	98	mm	-	
	B	100	mm	-	
	C	74	mm	-	
	$C_{a \min}$	15	mm	-	
	$C_{b \min}$	26	mm	-	
	$D_{a \max}$	442	mm	-	
	$D_{a \min}$	404	mm	-	
	$D_{b \min}$	439	mm	-	
	d_1	375	mm	-	
	$d_{a \max}$	329	mm	-	
	$d_{b \min}$	318	mm	-	
	$r_{1, 2 \min}$	5	mm	-	
	$r_{3, 4 \min}$	4	mm	-	
	$r_{a \max}$	5	mm	-	
	$r_{b \max}$	4	mm	-	
	重量	m	62400	g	质量
	基本额定载荷	C_R	1500000	N	基本额定动载荷，径向
		C_{0r}	2850000	N	基本额定静载荷，径向
计算系数	e	0.43		-	
	Y	1.38		-	
	Y_0	0.76		-	
疲劳极限载荷	C_{ur}	290000	N	疲劳极限载荷，径向	
极限转速	n_G	1380	r/min	极限转速	
参考转速	n_B	750	r/min	参考速度	
说明		T4GD300		根据 DIN ISO 355 的 对应型号	

FAG 32060-X图片

