

FAG 30217-A参数

疲劳极限载荷	C_{ur}	25500	N	疲劳极限载荷，径向	
极限转速	n_G	4850	r/min	极限转速	
参考转速	n_B	3200	r/min	参考速度	
说明		T3EB085		根据 DIN ISO 355 的 对应型号	
尺寸	d	85	mm	-	
	D	150	mm	-	
	T	30.5	mm	-	
	a	30	mm	-	
	B	28	mm	-	
	C	24	mm	-	
	$C_{a \min}$	5	mm	-	
	$C_{b \min}$	6.5	mm	-	
	$D_{a \max}$	140	mm	-	
	$D_{a \min}$	132	mm	-	
	$D_{b \min}$	141	mm	-	
	d_1	114.4	mm	-	
	$d_{a \max}$	97	mm	-	
	$d_{b \min}$	95	mm	-	
	$r_{1, 2 \min}$	2.5	mm	-	
	$r_{3, 4 \min}$	2	mm	-	
	$r_{a \max}$	2.5	mm	-	
	$r_{b \max}$	2	mm	-	
	重量	m	2110	g	质量
	基本额定载荷	C_r	178000	N	基本额定动载荷，径向
C_{0r}		224000	N	基本额定静载荷，径向	
计算系数	e	0.42		-	
	Y	1.43		-	

FAG 30217-A图片

