

### FAG 21319-E1-K-TVPB参数

|        |                    |        |       |            |
|--------|--------------------|--------|-------|------------|
| 尺寸     | d                  | 95     | mm    | -          |
|        | D                  | 200    | mm    | -          |
|        | B                  | 45     | mm    | -          |
|        | D <sub>1</sub>     | 169.4  | mm    | -          |
|        | D <sub>a max</sub> | 186    | mm    | -          |
|        | d <sub>2</sub>     | 124.3  | mm    | -          |
|        | d <sub>a min</sub> | 109    | mm    | -          |
|        | d <sub>s</sub>     | 4.8    | mm    | -          |
|        | n <sub>s</sub>     | 9.5    | mm    | -          |
|        | r <sub>a max</sub> | 2.5    | mm    | -          |
|        | r <sub>min</sub>   | 3      | mm    | -          |
|        | 重量                 | m      | 6530  | g          |
| 基本额定载荷 | C <sub>r</sub>     | 430000 | N     | 基本额定动载荷，径向 |
| 计算系数   | e                  | 0.22   |       | -          |
|        | Y <sub>1</sub>     | 3.04   |       | -          |
|        | Y <sub>2</sub>     | 4.53   |       | -          |
| 基本额定载荷 | C <sub>0r</sub>    | 460000 | N     | 基本额定静载荷，径向 |
| 计算系数   | Y <sub>0</sub>     | 2.97   |       | -          |
| 极限转速   | n <sub>G</sub>     | 4550   | r/min | 极限转速       |
| 参考转速   | n <sub>B</sub>     | 3300   | r/min | 参考速度       |
| 疲劳极限载荷 | C <sub>ur</sub>    | 47500  | N     | 疲劳极限载荷，径向  |

### FAG 21319-E1-K-TVPB图片



参考资料:<http://www.sozhou.com/p/7b90c48d.html>