

FAG 30307-A参数

尺寸	a	16	mm	-	
	B	21	mm	-	
	C	18	mm	-	
	$C_{a \text{ min}}$	3	mm	-	
	$C_{b \text{ min}}$	4.5	mm	-	
	$D_{a \text{ max}}$	71	mm	-	
	$D_{a \text{ min}}$	70	mm	-	
	$D_{b \text{ min}}$	74	mm	-	
	d_1	55.2	mm	-	
	$d_{a \text{ max}}$	45	mm	-	
	$d_{b \text{ min}}$	44	mm	-	
	$r_{1, 2 \text{ min}}$	2	mm	-	
	$r_{3, 4 \text{ min}}$	1.5	mm	-	
	$r_{a \text{ max}}$	2	mm	-	
	$r_{b \text{ max}}$	1.5	mm	-	
	重量	m	573	g	质量
	基本额定载荷	C_r	73000	N	基本额定动载荷, 径向
C_{0r}		75000	N	基本额定静载荷, 径向	
计算系数	e	0.31		-	
	Y	1.9		-	
	Y_0	1.05		-	
疲劳极限载荷	C_{ur}	8600	N	疲劳极限载荷, 径向	
极限转速	n_G	9700	r/min	极限转速	
参考转速	n_B	6600	r/min	参考速度	
说明		T2FB035		根据 DIN ISO 355 的 对应型号	
尺寸	d	35	mm	-	
	D	80	mm	-	

FAG 30307-A图片

