

### FAG 32215-A参数

尺寸	d	75	mm	-	
	D	130	mm	-	
	T	33.25	mm	-	
	a	29	mm	-	
	B	31	mm	-	
	C	27	mm	-	
	C <sub>a min</sub>	4	mm	-	
	C <sub>b min</sub>	6	mm	-	
	D <sub>a max</sub>	121	mm	-	
	D <sub>a min</sub>	115	mm	-	
	D <sub>b min</sub>	124	mm	-	
	d <sub>1</sub>	101.6	mm	-	
	d <sub>a max</sub>	85	mm	-	
	d <sub>b min</sub>	84	mm	-	
	r <sub>1, 2 min</sub>	2	mm	-	
	r <sub>3, 4 min</sub>	1.5	mm	-	
	r <sub>a max</sub>	2	mm	-	
	r <sub>b max</sub>	1.5	mm	-	
	重量	m	1930	g	质量
	基本额定载荷	C <sub>r</sub>	170000	N	基本额定动载荷，径向
C <sub>0r</sub>		227000	N	基本额定静载荷，径向	
计算系数	e	0.44		-	
	Y	1.38		-	
	Y <sub>0</sub>	0.76		-	
疲劳极限载荷	C <sub>ur</sub>	28000	N	疲劳极限载荷，径向	
极限转速	n <sub>G</sub>	5400	r/min	极限转速	
参考转速	n <sub>B</sub>	3200	r/min	参考速度	

FAG 32215-A图片

