



FAG NJ304-E-TVP2 + HJ304-E参数

参考转速	n_B	12100	r/min	参考速度
疲劳极限载荷	C_{ur}	3850	N	疲劳极限载荷, 径向
尺寸	d	20	mm	-
	D	52	mm	-
	B	15	mm	-
	B_1	4	mm	-
	B_2	6.5	mm	-
	D_1	42.4	mm	-
	$D_{a\ max}$	45	mm	-
	d_1	31.3	mm	-
	$d_{a\ max}$	27	mm	-
	$d_{a\ min}$	24	mm	-
	$d_{c\ min}$	33	mm	-
	E	45.5	mm	-
	F	27.5	mm	-
	$r_{1\ min}$	0.6	mm	-
	$r_{a\ max}$	1	mm	-
	$r_{a1\ max}$	0.6	mm	-
	r_{min}	1.1	mm	-
	s	1	mm	距离中心位置的轴向偏移
说明		HJ304-E		型号, L 型圈
重量	m	156	g	质量
	m_1	17	g	质量, L 型圈
基本额定载荷	C_r	37500	N	基本额定动载荷, 径向
	C_{0r}	27000	N	基本额定静载荷, 径向
极限转速	n_G	17200	r/min	极限转速

FAG NJ304-E-TVP2 + HJ304-E图片



参考资料:<http://www.sozhou.com/p/8772af1b.html>

