

### FAG S6302参数

|        |              |       |       |            |
|--------|--------------|-------|-------|------------|
| 尺寸     | d            | 15    | mm    | -          |
|        | D            | 42    | mm    | -          |
|        | B            | 13    | mm    | -          |
|        | $D_1$        | 33.5  | mm    | -          |
|        | $D_{a \max}$ | 36.4  | mm    | -          |
|        | $d_1$        | 23.6  | mm    | -          |
|        | $d_{a \min}$ | 20.6  | mm    | -          |
|        | $r_{a \max}$ | 1     | mm    | -          |
|        | $r_{\min}$   | 1     | mm    | -          |
| 重量     | m            | 88    | g     | 质量         |
| 基本额定载荷 | $C_r$        | 9710  | N     | 基本额定动载荷，径向 |
|        | $C_{0r}$     | 4370  | N     | 基本额定静载荷，径向 |
| 极限转速   | $n_G$        | 25000 | r/min | 极限转速       |
| 参考转速   | $n_B$        | 17500 | r/min | 参考速度       |
| 疲劳极限载荷 | $C_{ur}$     | 350   | N     | 疲劳极限载荷，径向  |

### FAG S6302图片





参考资料:<http://www.sozhou.com/p/87a4c8fe.html>