

## NSK NU248参数

|        |      |           |       |      |
|--------|------|-----------|-------|------|
| 型号     | 型号   | NU248     |       | -    |
| 外形尺寸   | SD   | 240       | mm    | 内径   |
|        | D    | 440       | mm    | 外径   |
|        | B    | 72        | mm    | 宽度   |
|        | R    | 4.0       | mm    | (最小) |
|        | R1   | 4.0       | mm    | (最小) |
|        | FW   | 295.0     | mm    | -    |
|        | EW   | 0.0       | mm    | -    |
| 基本额定载荷 | CR1  | 935000    | N     | 动载荷  |
|        | COR1 | 1340000   | N     | 静载荷  |
|        | CR2  | 95500     | kgf   | 动载荷  |
|        | COR2 | 136000    | kgf   | 静载荷  |
| 极限转速   | LG   | 1300      | 1/min | 脂润滑  |
|        | LO   | 1600      | 1/min | 油润滑  |
| 安装尺寸   | DA1  | 256.0     | mm    | (最小) |
|        | DBB1 | 256.00000 | mm    | (最小) |
|        | DBB2 | 289       | mm    | (最大) |
|        | DC   | 298       | mm    | (最小) |
|        | DD1  | 316       | mm    | (最小) |
|        | DA2  | 424.0     | mm    | (最大) |
|        | DB1  | 0.0       | mm    | (最小) |
|        | DB2  | 0.0       | mm    | (最小) |
|        | RA   | 3.0       | mm    | (最大) |
|        | RB   | 3.0       | mm    | (最大) |
| 重量     | MASS | 50400     | g     | 重量   |

## NSK NU248图片

参考资料:<http://www.sozhou.com/p/8aa4cd6e.html>

