

## FAG 33112参数

计算系数	Y	1.51		-
	$Y_0$	0.83		-
疲劳极限载荷	$C_{ur}$	21500	N	疲劳极限载荷，径向
极限转速	$n_G$	6900	r/min	极限转速
参考转速	$n_B$	4000	r/min	参考速度
说明		T3CE060		根据 DIN ISO 355 的 对应型号
尺寸	d	60	mm	-
	D	100	mm	-
	T	30	mm	-
	a	23	mm	-
	B	30	mm	-
	C	23	mm	-
	$C_{a \min}$	5	mm	-
	$C_{b \min}$	7	mm	-
	$D_{a \max}$	93	mm	-
	$D_{a \min}$	88	mm	-
	$D_{b \min}$	96	mm	-
	$d_1$	81.3	mm	-
	$d_{a \max}$	67	mm	-
	$d_{b \min}$	67	mm	-
	$r_{1, 2 \min}$	1.5	mm	-
	$r_{3, 4 \min}$	1.5	mm	-
	$r_{a \max}$	1.5	mm	-
	$r_{b \max}$	1.5	mm	-
重量	m	1010	g	质量
基本额定载荷	$C_r$	116000	N	基本额定动载荷，径向
	$C_{0r}$	171000	N	基本额定静载荷，径向

FAG 33112图片

