

NSK NUP230参数

| | | | | | |
|--------|------|-----------|--------|------|----|
| 极限转速 | L0 | 2800 | 1/min | 油润滑 | |
| 安装尺寸 | DA1 | 163.0 | mm | (最小) | |
| | DBB1 | 163.00000 | mm | (最小) | |
| | DBB2 | 177 | mm | (最大) | |
| | DC | 184 | mm | (最小) | |
| | DD1 | 196 | mm | (最小) | |
| | DA2 | 257.0 | mm | (最大) | |
| | DB1 | 0.0 | mm | (最小) | |
| | DB2 | 0.0 | mm | (最小) | |
| | RA | 2.5 | mm | (最大) | |
| | RB | 2.5 | mm | (最大) | |
| | 重量 | MASS | 10400 | g | 重量 |
| | 型号 | 型号 | NUP230 | | - |
| 外形尺寸 | SD | 150 | mm | 内径 | |
| | D | 270 | mm | 外径 | |
| | B | 45 | mm | 宽度 | |
| | R | 3.0 | mm | (最小) | |
| | R1 | 3.0 | mm | (最小) | |
| | FW | 182.0 | mm | - | |
| | EW | 0.0 | mm | - | |
| 基本额定载荷 | CR1 | 345000 | N | 动载荷 | |
| | COR1 | 435000 | N | 静载荷 | |
| | CR2 | 35000 | kgf | 动载荷 | |
| | COR2 | 44500 | kgf | 静载荷 | |
| 极限转速 | LG | 2200 | 1/min | 脂润滑 | |

NSK NUP230图片

参考资料:<http://www.sozhou.com/p/90723076.html>

