

FAG 31311-A参数

尺寸	$r_{b \max}$	2	mm	-
重量	m	1570	g	质量
基本额定载荷	C_r	123000	N	基本额定动载荷, 径向
	C_{0r}	139000	N	基本额定静载荷, 径向
计算系数	e	0.83		-
	Y	0.73		-
	Y_0	0.4		-
疲劳极限载荷	C_{ur}	16400	N	疲劳极限载荷, 径向
极限转速	n_G	5900	r/min	极限转速
参考转速	n_B	4100	r/min	参考速度
说明		T7FB055		根据 DIN ISO 355 的 对应型号
尺寸	d	55	mm	-
	D	120	mm	-
	T	31.5	mm	-
	a	39	mm	-
	B	29	mm	-
	C	21	mm	-
	$C_{a \min}$	4	mm	-
	$C_{b \min}$	10.5	mm	-
	$D_{a \max}$	110	mm	-
	$D_{a \min}$	94	mm	-
	$D_{b \min}$	113	mm	-
	d_1	88	mm	-
	$d_{a \max}$	68	mm	-
	$d_{b \min}$	65	mm	-
	$r_{1, 2 \min}$	2.5	mm	-
	$r_{3, 4 \min}$	2	mm	-

FAG 31311-A图片

