

### FAG NNU4926-S-M-SP参数

|        |                    |        |       |             |
|--------|--------------------|--------|-------|-------------|
| 尺寸     | d                  | 130    | mm    | -           |
|        | D                  | 180    | mm    | -           |
|        | B                  | 50     | mm    | -           |
|        | D <sub>1</sub>     | 162    | mm    | -           |
|        | D <sub>a max</sub> | 172    | mm    | -           |
|        | d <sub>a min</sub> | 138    | mm    | -           |
|        | d <sub>s</sub>     | 3.2    | mm    | -           |
|        | F                  | 146    | mm    | -           |
|        | n <sub>s</sub>     | 6.5    | mm    | -           |
|        | r <sub>a max</sub> | 1.5    | mm    | -           |
|        | r <sub>min</sub>   | 1.5    | mm    | -           |
|        | s                  | 3      | mm    | 距离中心位置的轴向偏移 |
| 重量     | m                  | 4000   | g     | 质量          |
| 基本额定载荷 | C <sub>r</sub>     | 190000 | N     | 基本额定动载荷，径向  |
|        | C <sub>0r</sub>    | 390000 | N     | 基本额定静载荷，径向  |
| 极限转速   | n <sub>G</sub>     | 3800   | r/min | 极限转速        |
| 疲劳极限载荷 | C <sub>ur</sub>    | 45000  | N     | 疲劳极限载荷，径向   |

### FAG NNU4926-S-M-SP图片



