

### FAG NJ2240-E-M1 参数

尺寸	d	200	mm	-
	D	360	mm	-
	B	98	mm	-
	B <sub>1</sub>	14	mm	-
	B <sub>2</sub>	28	mm	-
	D <sub>1</sub>	312.9	mm	-
	D <sub>a max</sub>	343	mm	-
	d <sub>1</sub>	256.3	mm	-
	d <sub>a max</sub>	240	mm	-
	d <sub>a min</sub>	217	mm	-
	d <sub>c min</sub>	261	mm	-
	F	241	mm	-
	r <sub>1 min</sub>	4	mm	-
	r <sub>a max</sub>	3	mm	-
	r <sub>a1 max</sub>	3	mm	-
	r <sub>min</sub>	4	mm	-
	s	8.2	mm	距离中心位置的轴向偏移
重量	m	45300	g	质量
基本额定载荷	C <sub>r</sub>	1220000	N	基本额定动载荷，径向
	C <sub>0r</sub>	1880000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	2850	r/min	极限转速
参考转速	n <sub>B</sub>	1200	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	225000	N	疲劳极限载荷，径向

### FAG NJ2240-E-M1 图片





参考资料:<http://www.sozhou.com/p/9b1640ae.html>