

TIMKEN 23092/23256参数

轴承类型	Bearing Type	TRB		-	
子类	Bearing Subtype	TS		-	
尺寸	Cone (Inner)	23092		内圈	
	Cup (Outer)	23256		外圈	
尺寸	d	23.8125	mm	内径	
	D	65.0875	mm	外径	
	T	22.225	mm	宽度	
	额定载荷	C1	54713.1	N	一百万转动态径向载荷
		C90	14145.3	N	九千万转动态径向载荷
		Ca90	17748.4	N	九千万转单列轴承动态轴向载荷
C0		55602.8	N	静态额定载荷	
尺寸	$K = 0.39 / \tan(\text{contact angle})$	0.80		系数	
	$e = 1.5 * \tan(\text{contact angle})$	0.73		系数	
	$Y = 0.4 / \tan(\text{contact angle})$	0.82		系数	
几何结构系数	Cg	0.0700		几何系数	
尺寸	B	21.463	mm	内圈宽度	
	R	1.524	mm	最大轴肩倒角半径	
	db	38.608	mm	轴肩直径	
	da	34.544	mm	轴肩直径	
	Aa	3.81	mm	保持架（负值表示保持架超出内圈大端面）	
	Ab	2.032	mm	保持架（负值表示保持架没超出内圈小端面）	
	C	15.875	mm	外圈宽度	
	r	1.524	mm	最大轴承座挡肩圆角半径	
	Db	53.086	mm	轴承座挡肩直径	
	Da	62.992	mm	轴承座挡肩直径	
	a	-2.286	mm	有效中心位置	
	重量	Assembly Weight	367.41	g	-

TIMKEN 23092/23256图片







参考资料:<http://www.sozhou.com/p/a14f982b.html>

