

## FAG 30224-A参数

尺寸	T	43.5	mm	-	
	a	44	mm	-	
	B	40	mm	-	
	C	34	mm	-	
	$C_{a \text{ min}}$	6	mm	-	
	$C_{b \text{ min}}$	9.5	mm	-	
	$D_{a \text{ max}}$	203	mm	-	
	$D_{a \text{ min}}$	187	mm	-	
	$D_{b \text{ min}}$	201	mm	-	
	$d_1$	163	mm	-	
	$d_{a \text{ max}}$	140	mm	-	
	$d_{b \text{ min}}$	132	mm	-	
	$r_{1, 2 \text{ min}}$	3	mm	-	
	$r_{3, 4 \text{ min}}$	2.5	mm	-	
	$r_{a \text{ max}}$	3	mm	-	
	$r_{b \text{ max}}$	2.5	mm	-	
	重量	m	6250	g	质量
	基本额定载荷	$C_r$	330000	N	基本额定动载荷，径向
		$C_{0r}$	445000	N	基本额定静载荷，径向
	计算系数	e	0.44		-
Y		1.38		-	
$Y_0$		0.76		-	
疲劳极限载荷	$C_{ur}$	56000	N	疲劳极限载荷，径向	
极限转速	$n_G$	3300	r/min	极限转速	
参考转速	$n_B$	2460	r/min	参考速度	
说明		T4FB120		根据 DIN ISO 355 的 对应型号	
尺寸	d	120	mm	-	

FAG 30224-A图片

