

NACHI 7340BDT参数

| | | | | |
|--------|----------|---------|-------|------|
| 外形尺寸 | d | 200 | mm | 内径 |
| | D | 420 | mm | 外径 |
| | B | 80 | mm | 宽度 |
| | r | 5~8 | mm | 轴向 |
| | r | 5~10 | mm | 轴向 |
| | r1 | 2~3.5 | mm | 轴向 |
| | r1 | 2~5 | mm | 轴向 |
| | 载荷中心 | a | 90.1 | mm |
| 安装尺寸 | da1(min) | 222 | mm | (最小) |
| | da2(min) | 210 | mm | (最小) |
| | Da1(max) | 398 | mm | (最大) |
| | Da2(max) | 410 | mm | (最大) |
| | ra(max) | 4 | mm | (最大) |
| | ra1(max) | 2 | mm | (最大) |
| 重量 | Mass | 107400 | g | 重量 |
| 基本额定载荷 | Cr | 725000 | N | 动载荷 |
| | Cor | 1240000 | N | 静载荷 |
| 极限速度 | Grease | 1000 | r/min | 脂润滑 |
| | Oil | 1300 | r/min | 油润滑 |

NACHI 7340BDT图片

参考资料:<http://www.sozhou.com/p/acd41b95.html>

