

### FAG NU340-E-TB-M1参数

尺寸	d	200	mm	-
	D	420	mm	-
	B	80	mm	-
	D <sub>1</sub>	347.6	mm	-
	D <sub>a max</sub>	400	mm	-
	d <sub>a max</sub>	255	mm	-
	d <sub>a min</sub>	220	mm	-
	d <sub>b min</sub>	261	mm	-
	E	370	mm	-
	F	258	mm	-
	r <sub>1 min</sub>	5	mm	-
	r <sub>a max</sub>	4	mm	-
	r <sub>al max</sub>	4	mm	-
	r <sub>min</sub>	5	mm	-
	s	6.3	mm	距离中心位置的轴向偏移
重量	m	57300	g	质量
基本额定载荷	C <sub>r</sub>	1180000	N	基本额定动载荷，径向
	C <sub>0r</sub>	1520000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	2410	r/min	极限转速
参考转速	n <sub>B</sub>	1340	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	107000	N	疲劳极限载荷，径向

### FAG NU340-E-TB-M1图片



参考资料:<http://www.sozhou.com/p/b305d302.html>

