

### NACHI NU2306E参数

|        |           |         |       |      |
|--------|-----------|---------|-------|------|
| 外形尺寸   | d         | 30      | mm    | 内径   |
|        | D         | 72      | mm    | 外径   |
|        | B         | 27      | mm    | 宽度   |
|        | r         | 1.1~2   | mm    | 轴向   |
|        | r         | 1.1~3.5 | mm    | 轴向   |
|        | r1        | 1.1~2   | mm    | 轴向   |
|        | r1        | 1.1~3.5 | mm    | 轴向   |
|        | Fw        | 40.5    | mm    | -    |
| 安装尺寸   | db (min)  | 37      | mm    | (最小) |
|        | db (max)  | 40      | mm    | (最大) |
|        | dc (max)  | 44      | mm    | (最大) |
|        | Da (max)  | 65      | mm    | (最大) |
|        | ra (max)  | 1       | mm    | (最大) |
|        | ra1 (max) | 1       | mm    | (最大) |
| 重量     | Mass      | 585     | g     | 重量   |
| 基本额定载荷 | Cr        | 74500   | N     | 动载荷  |
|        | Cor       | 77500   | N     | 静载荷  |
| 极限速度   | Grease    | 8000    | r/min | 脂润滑  |
|        | Oil       | 9500    | r/min | 油润滑  |

### NACHI NU2306E图片

参考资料:<http://www.sozhou.com/p/baf2b56a.html>

