

FAG 30213-A参数

尺寸	$r_{1, 2 \text{ min}}$	2	mm	-
	$r_{3, 4 \text{ min}}$	1.5	mm	-
	$r_{a \text{ max}}$	2	mm	-
	$r_{b \text{ max}}$	1.5	mm	-
重量	m	1270	g	质量
基本额定载荷	C_r	119000	N	基本额定动载荷, 径向
	C_{0r}	142000	N	基本额定静载荷, 径向
计算系数	e	0.4		-
	Y	1.48		-
	Y_0	0.81		-
疲劳极限载荷	C_{ur}	16600	N	疲劳极限载荷, 径向
极限转速	n_G	6100	r/min	极限转速
参考转速	n_B	3850	r/min	参考速度
说明		T3EB065		根据 DIN ISO 355 的 对应型号
尺寸	D	120	mm	-
	T	24.75	mm	-
	a	23	mm	-
	B	23	mm	-
	C	20	mm	-
	$C_{a \text{ min}}$	4	mm	-
	$C_{b \text{ min}}$	4.5	mm	-
	$D_{a \text{ max}}$	111	mm	-
	$D_{a \text{ min}}$	106	mm	-
	$D_{b \text{ min}}$	113	mm	-
	d_1	90	mm	-
	$d_{a \text{ max}}$	77	mm	-
	$d_{b \text{ min}}$	74	mm	-

FAG 30213-A图片

