

FAG 32006-X参数

尺寸	d	30	mm	-	
	D	55	mm	-	
	T	17	mm	-	
	a	14	mm	-	
	B	17	mm	-	
	C	13	mm	-	
	$C_a \text{ min}$	3	mm	-	
	$C_b \text{ min}$	4	mm	-	
	$D_a \text{ max}$	49	mm	-	
	$D_a \text{ min}$	48	mm	-	
	$D_b \text{ min}$	52	mm	-	
	d_1	44.1	mm	-	
	$d_a \text{ max}$	35	mm	-	
	$d_b \text{ min}$	36	mm	-	
	$r_{1, 2} \text{ min}$	1	mm	-	
	$r_{3, 4} \text{ min}$	1	mm	-	
	$r_a \text{ max}$	1	mm	-	
	$r_b \text{ max}$	1	mm	-	
	重量	m	195	g	质量
	基本额定载荷	C_r	38500	N	基本额定动载荷, 径向
C_{0r}		46500	N	基本额定静载荷, 径向	
计算系数	e	0.43		-	
	Y	1.39		-	
	Y_0	0.77		-	
疲劳极限载荷	C_{ur}	5300	N	疲劳极限载荷, 径向	
极限转速	n_G	13300	r/min	极限转速	
参考转速	n_B	7900	r/min	参考速度	

FAG 32006-X图片

