

FAG 230/500-B-K-MB + H30/500参数

尺寸	D_m	580	mm	-
	d	500	mm	-
	$d_{a \max}$	550	mm	-
	$d_{b \min}$	519	mm	-
	d_s	12.5	mm	-
	l	247	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	5	mm	-
	r_{\min}	6	mm	-
说明		H30/500		质量, 紧定套
重量	m	219000	g	质量
	m_1	85200	g	质量, 紧定套
基本额定载荷	C_r	3900000	N	基本额定动载荷, 径向
计算系数	e	0.22		-
	Y_1	3.01		-
	Y_2	4.48		-
基本额定载荷	C_{0r}	8500000	N	基本额定静载荷, 径向
计算系数	Y_0	2.94		-
极限转速	n_G	890	r/min	极限转速
参考转速	n_B	520	r/min	参考速度
疲劳极限载荷	C_{ur}	510000	N	疲劳极限载荷, 径向
尺寸	d_{1H}	470	mm	-
	D	720	mm	-
	B	167	mm	-
	$B_{a \min}$	18	mm	-
	c	68	mm	-
	c_1	83	mm	-

D_1	653.5	mm	-
$D_{a \max}$	697	mm	-

FAG 230/500-B-K-MB + H30/500图片

