

### FAG NU206-E-TVP2参数

尺寸	d	30	mm	-
	D	62	mm	-
	B	16	mm	-
	D <sub>1</sub>	52.5	mm	-
	D <sub>a max</sub>	56	mm	-
	d <sub>a max</sub>	37	mm	-
	d <sub>a min</sub>	34	mm	-
	d <sub>b min</sub>	40	mm	-
	E	55.5	mm	-
	F	37.5	mm	-
	r <sub>l min</sub>	0.6	mm	-
	r <sub>a max</sub>	1	mm	-
	r <sub>al max</sub>	0.6	mm	-
	r <sub>min</sub>	1	mm	-
	s	1.5	mm	距离中心位置的轴向偏移
重量	m	207	g	质量
基本额定载荷	C <sub>r</sub>	46000	N	基本额定动载荷，径向
	C <sub>0r</sub>	37500	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	14200	r/min	极限转速
参考转速	n <sub>B</sub>	9800	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	4350	N	疲劳极限载荷，径向

### FAG NU206-E-TVP2图片



参考资料:<http://www.sozhou.com/p/c8e9f145.html>

