

FAG 33212参数

尺寸	d	60	mm	-	
	D	110	mm	-	
	T	38	mm	-	
	a	28	mm	-	
	B	38	mm	-	
	C	29	mm	-	
	$C_{a \min}$	6	mm	-	
	$C_{b \min}$	9	mm	-	
	$D_{a \max}$	101	mm	-	
	$D_{a \min}$	93	mm	-	
	$D_{b \min}$	105	mm	-	
	d_1	86.2	mm	-	
	$d_{a \max}$	69	mm	-	
	$d_{b \min}$	69	mm	-	
	$r_{1, 2 \min}$	2	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	2	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1550	g	质量
	基本额定载荷	C_r	169000	N	基本额定动载荷，径向
C_{0r}		237000	N	基本额定静载荷，径向	
计算系数	e	0.4		-	
	Y	1.48		-	
	Y_0	0.82		-	
疲劳极限载荷	C_{ur}	29500	N	疲劳极限载荷，径向	
极限转速	n_G	6300	r/min	极限转速	
参考转速	n_B	4050	r/min	参考速度	

FAG 33212图片

