

## NSK NJ412参数

|      |        |          |        |      |     |
|------|--------|----------|--------|------|-----|
| 极限转速 | L0     | 5300     | 1/min  | 油润滑  |     |
| 安装尺寸 | DA1    | 71.0     | mm     | (最小) |     |
|      | DBB1   | 71.00000 | mm     | (最小) |     |
|      | DBB2   | 80       | mm     | (最大) |     |
|      | DC     | 85       | mm     | (最小) |     |
|      | DD1    | 94       | mm     | (最小) |     |
|      | DA2    | 139.0    | mm     | (最大) |     |
|      | DB1    | 139.0    | mm     | (最小) |     |
|      | DB2    | 130.0    | mm     | (最小) |     |
|      | RA     | 2.0      | mm     | (最大) |     |
|      | RB     | 2.0      | mm     | (最大) |     |
|      | 重量     | MASS     | 3040   | g    | 重量  |
|      | 型号     | 型号       | NJ412  |      | -   |
| 外形尺寸 | SD     | 60       | mm     | 内径   |     |
|      | D      | 150      | mm     | 外径   |     |
|      | B      | 35       | mm     | 宽度   |     |
|      | R      | 2.1      | mm     | (最小) |     |
|      | R1     | 2.1      | mm     | (最小) |     |
|      | FW     | 83.0     | mm     | -    |     |
|      | EW     | 127.0    | mm     | -    |     |
|      | 基本额定载荷 | CR1      | 167000 | N    | 动载荷 |
| COR1 |        | 168000   | N      | 静载荷  |     |
| CR2  |        | 17100    | kgf    | 动载荷  |     |
| COR2 |        | 17200    | kgf    | 静载荷  |     |
| 极限转速 | LG     | 4300     | 1/min  | 脂润滑  |     |

## NSK NJ412图片

参考资料:<http://www.sozhou.com/p/cfa73f81.html>

