

FAG 32310-B参数

尺寸	$d_{a \max}$	60	mm	-
	$d_{b \min}$	60	mm	-
	$r_{1, 2 \min}$	2.5	mm	-
	$r_{3, 4 \min}$	2	mm	-
	$r_{a \max}$	2.5	mm	-
	$r_{b \max}$	2	mm	-
重量	m	1940	g	质量
基本额定载荷	$C_r$	165000	N	基本额定动载荷，径向
尺寸	d	50	mm	-
	D	110	mm	-
	T	42.25	mm	-
	a	33	mm	-
	B	40	mm	-
	C	33	mm	-
	$C_{a \min}$	5	mm	-
	$C_{b \min}$	9	mm	-
	$D_{a \max}$	100	mm	-
	$D_{a \min}$	83	mm	-
	$D_{b \min}$	103	mm	-
	$d_1$	82.6	mm	-
基本额定载荷	$C_{0r}$	223000	N	基本额定静载荷，径向
计算系数	e	0.55		-
	Y	1.1		-
	$Y_0$	0.6		-
疲劳极限载荷	$C_{ur}$	28000	N	疲劳极限载荷，径向
极限转速	$n_G$	6500	r/min	极限转速
参考转速	$n_B$	4650	r/min	参考速度

FAG 32310-B图片

