

FAG 23144-B-K-MB + H3144X参数

尺寸	$d_{1H}$	200	mm	-
	D	370	mm	-
	B	120	mm	-
	$B_{a \min}$	10	mm	-
	c	35	mm	-
	$D_1$	319.2	mm	-
	$D_{a \max}$	353	mm	-
	$D_m$	280	mm	-
	d	220	mm	-
	$d_{a \max}$	253	mm	-
	$d_{b \min}$	233	mm	-
	$d_s$	9.5	mm	-
	l	161	mm	-
	$n_s$	17.7	mm	-
	$r_{a \max}$	3	mm	-
	$r_{\min}$	4	mm	-
说明		H3144X		质量, 紧定套
重量	m	52000	g	质量
	$m_1$	15700	g	质量, 紧定套
基本额定载荷	$C_r$	1630000	N	基本额定动载荷, 径向
计算系数	e	0.33		-
	$Y_1$	2.03		-
	$Y_2$	3.02		-
基本额定载荷	$C_{0r}$	2900000	N	基本额定静载荷, 径向
疲劳极限载荷	$C_{ur}$	165000	N	疲劳极限载荷, 径向
计算系数	$Y_0$	1.98		-
极限转速	$n_G$	1820	r/min	极限转速

FAG 23144-B-K-MB + H3144X图片

