

NACHI 29422EX参数

| | | | | |
|--------|-----------|---------|-------|------|
| 外形尺寸 | d | 110 | mm | 内径 |
| | D | 230 | mm | 外径 |
| | T | 73 | mm | 宽度 |
| | r | 3~5.5 | mm | 倒角 |
| 参考尺寸 | d1 | 199.6 | mm | - |
| | D1 | 153.4 | mm | - |
| | B | 48 | mm | - |
| | B1 | 64.4 | mm | - |
| | C | 35 | mm | - |
| | A | 69 | mm | - |
| 安装尺寸 | da (min) | 165 | mm | (最小) |
| | Da (max) | 190 | mm | (最大) |
| | ra (max) | 2.5 | mm | (最大) |
| | db1 (max) | 119.5 | mm | (最大) |
| | db2 (max) | 120 | mm | (最大) |
| 重量 | Mass | 14000 | g | 重量 |
| 基本额定载荷 | Ca | 1060000 | N | 动载荷 |
| | Coa | 3150000 | N | 静载荷 |
| 极限速度 | Grease | 950 | r/min | 脂润滑 |
| | Oil | 1500 | r/min | 油润滑 |

NACHI 29422EX图片

参考资料:<http://www.sozhou.com/p/e84f59c3.html>

