

**FAG 292/1320-E-MB参数**

尺寸	A	698	mm	-
	D <sub>1</sub>	1411	mm	-
	D <sub>a max</sub>	1500	mm	-
	D <sub>b min</sub>	1632	mm	-
	d <sub>1</sub>	1540	mm	-
	d <sub>a min</sub>	1425	mm	-
	d <sub>b max</sub>	1298	mm	-
	r <sub>a max</sub>	8	mm	-
	r <sub>min</sub>	9.5	mm	-
	T <sub>1</sub>	113	mm	-
	T <sub>2</sub>	78	mm	-
	T <sub>3</sub>	131	mm	-
	T <sub>4</sub>	154	mm	-
重量	m	1002200	g	质量
基本额定载荷	C <sub>a</sub>	12200000	N	基本额定动载荷, 轴向
	C <sub>0a</sub>	75000000	N	基本额定静载荷, 轴向
极限转速	n <sub>G</sub>	355	r/min	极限转速
参考转速	n <sub>B</sub>	186	r/min	参考速度
疲劳极限载荷	C <sub>ua</sub>	0	N	疲劳极限载荷, 轴向
尺寸	d	1250	mm	-
	D	1610	mm	-
	T	228	mm	-

**FAG 292/1320-E-MB图片**



参考资料:<http://www.sozhou.com/p/e9731de3.html>