

FAG HCB71909-C-2RSD-T-P4S参数

|        |               |       |       |             |
|--------|---------------|-------|-------|-------------|
| 尺寸     | B             | 12    | mm    | -           |
|        | a             | 14    | mm    | -           |
|        | $D_a$ H12     | 63.5  | mm    | -           |
|        | $d_a$ h12     | 50    | mm    | -           |
|        | $r_{1\ min}$  | 0.6   | mm    | -           |
|        | $r_{a\ max}$  | 0.6   | mm    | -           |
|        | $r_{a1\ max}$ | 0.6   | mm    | -           |
|        | $r_{\min}$    | 0.6   | mm    | -           |
| 重量     | m             | 114   | g     | 质量          |
| 基本额定载荷 | $C_r$         | 19100 | N     | 基本额定动载荷, 径向 |
|        | $C_{0r}$      | 7800  | N     | 基本额定静载荷, 径向 |
| 极限转速   | $n_{G\ Fett}$ | 28000 | r/min | 脂润滑时的极限转速   |
| 尺寸     | d             | 45    | mm    | -           |
|        | D             | 68    | mm    | -           |
| 疲劳极限载荷 | $C_{ur}$      | 820   | N     | 疲劳极限载荷, 径向  |

FAG HCB71909-C-2RSD-T-P4S图片



