

FAG 23288-B-K-MB + H3288参数

尺寸	d_{1H}	410	mm	-
	D	790	mm	-
	B	280	mm	-
	$B_{a \min}$	17	mm	-
	c	70	mm	-
	c_1	89	mm	-
	D_1	669.3	mm	-
	$D_{a \max}$	758	mm	-
	D_m	560	mm	-
	d	440	mm	-
	$d_{a \max}$	516	mm	-
	$d_{b \min}$	469	mm	-
	d_s	12.5	mm	-
	l	361	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	6	mm	-
	r_{\min}	7.5	mm	-
说明		H3288		质量, 紧定套
重量	m	586000	g	质量
	m_1	120000	g	质量, 紧定套
基本额定载荷	C_r	7100000	N	基本额定动载荷, 径向
计算系数	e	0.37		-
	Y_1	1.8		-
	Y_2	2.69		-
基本额定载荷	C_{0r}	13400000	N	基本额定静载荷, 径向
计算系数	Y_0	1.76		-
极限转速	n_G	720	r/min	极限转速

参考转速	n_B	320	r/min	参考速度
疲劳极限载荷	C_{ur}	990000	N	疲劳极限载荷，径向

FAG 23288-B-K-MB + H3288图片

