

FAG 23964-K-MB + AH3964G参数

尺寸	d_{1H}	300	mm	-	
	D	440	mm	-	
	B	90	mm	-	
	a	7	mm	-	
	b	21	mm	-	
	D_1	406.2	mm	-	
	$D_{a\ max}$	427.6	mm	-	
	d	320	mm	-	
	d_{2G}	Tr340x5		-	
	$d_{a\ min}$	332.4	mm	-	
	d_s	9.5	mm	-	
	l	112	mm	-	
	n_s	17.7	mm	-	
	$r_{a\ max}$	2.5	mm	-	
	r_{min}	3	mm	-	
	说明		AH3964G		型号, 退卸套
	重量	m	41000	g	质量
m_1		11500	g	质量, 退卸套	
基本额定载荷	C_r	1310000	N	基本额定动载荷, 径向	
计算系数	e	0.19		-	
	Y_1	3.62		-	
	Y_2	5.39		-	
基本额定载荷	C_{0r}	2750000	N	基本额定静载荷, 径向	
计算系数	Y_0	3.54		-	
极限转速	n_G	1700	r/min	极限转速	
参考转速	n_B	940	r/min	参考速度	
疲劳极限载荷	C_{ur}	201000	N	疲劳极限载荷, 径向	

FAG 23964-K-MB + AH3964G图片



参考资料:<http://www.sozhou.com/p/f856e306.html>