

NSK 51317参数

| | | | | |
|--------|------|--------|-------|------|
| 外形尺寸 | T | 49 | mm | 宽度 |
| | T3 | 53.1 | mm | - |
| | T4 | 58 | mm | - |
| | SR | 1.5 | mm | (最小) |
| 基本额定载荷 | CAN | 207000 | N | 动载荷 |
| | COAN | 490000 | N | 静载荷 |
| | CA | 21100 | kgf | 动载荷 |
| | COA | 50000 | kgf | 静载荷 |
| 极限转速 | GRE | 1100 | 1/min | 脂润滑 |
| | OIL | 1700 | 1/min | 油润滑 |
| 尺寸 | SD1 | 150 | mm | - |
| | D1 | 88 | mm | - |
| | D2 | 115 | mm | - |
| | D3 | 155 | mm | - |
| | SB | 17.5 | mm | - |
| | A | 43.0 | mm | - |
| | R | 112 | mm | - |
| 安装尺寸 | SDA | 124 | mm | (最小) |
| | DA | 111 | mm | (最大) |
| | SRA | 1.5 | mm | (最大) |
| 重量 | MASS | 3570 | g | 重量 |
| 型号 | 型号 | 51317 | | - |
| 外形尺寸 | SD | 85 | mm | 内径 |
| | D | 150 | mm | 外径 |

NSK 51317图片



参考资料:<http://www.sozhou.com/p/fdee1933.html>

